

## Comparison Between kBox4 Systems

	Active	Lite	Pro
Footprint in cm (inches)			
width	76 (30")	76 (30")	98 (38,5")
depth	51 (20")	51 (20")	63 (29")
height	21 (8.5")	21 (8.5")	23 (9")
Top surface in cm (inches)			
width	68.5 (27")	68.5 (27")	90 (35.5")
depth	43.5 (17")	43.5 (17")	55 (21.5")
area [sq.m]	0.29	0.29	0.50
weight	14.5 kg (32 lbs)	9.5 kg (21 lbs)	15.5 kg (34 lbs)
Materials			
chassi	steel	aluminium	aluminium
flywheel	steel	steel	steel
color	bronze	brown	brown
Features			
kMeter II built-in	optional*	yes	yes
drive belt autoretract	yes	yes	yes
quick change flywheel	yes	yes	yes
foot support option**	yes	yes	yes
no. of flywheels mounted	1-2	1-4	1-4
inertia range kgm <sup>2</sup>	0.01 - 0.10	0.01 - 0.20	0.01 - 0.28
inertia factor (min to max)	x10	x20	x28
angle adjuster	***	yes	yes
can attach foot support	yes	yes	yes
Flywheel options			
0.010	yes	yes	yes
0.025	yes	yes	yes
0.050	yes	yes	yes
0.070	-	-	yes

\*) Active is kMeter II ready. It can be pre-installed from factory or later by customer.

\*\*\*) Pro has a larger platform and more positions for individual adjustment of the foot blocks.

\*\*\*) Angle adjuster for Active will be released later 2018.